(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 16 June 2005 (16.06.2005)

PCT

(10) International Publication Number WO 2005/055140 A1

(51) International Patent Classification7:

G06T 5/00

(21) International Application Number:

PCT/IB2004/052518

(22) International Filing Date:

23 November 2004 (23.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03104503.2

2 December 2003 (02.12.2003)


- (71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Steindamm 94, 20099 Hamburg (DE).
- (71) Applicant (for all designated States except DE, US): KONINKLIJKE PHILIPS ELECTRONICS N. V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Bindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MAACK,

Hanns-Ingo [DE/DE]; c/o Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE). KLOESSNER, Andreas [DE/DE]; c/o Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).

- (74) Agents: MEYER, Michael et al.; Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SB, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: A DEVICE AND METHOD FOR CORRECTING DEFECTS IN X-RAY IMAGES



(57) Abstract: The invention relates to a method for correcting defects in X-ray images in which potentially defective picture elements (p) are identified in X-ray images (I), which are created during normal operation, by comparing the value (W(p)) of said picture elements with corresponding values in a neighborhood (n(p)). If a picture element (p) has been classified as "potentially defective" in more than a specified percentage of X-ray images, it is entered in a defect map which is refreshed on a continuous basis. The defect map can then be used to correct other X-ray images.